



Shaver Industries

20 Steckle Place, Kitchener, ON N2E 2C3
Ph 1(888) 766 8328
www.shaverinc.com

Assembly Instructions Vertical Vinyl Curtain Door “Face Mount”

Valued Shaver's Customer: We have pre-assembled the roller, valence, and bracketry components for your Motorized Door. This should dramatically simplify the installation procedure. While the installation is very straightforward, please note the following details.

System Overview:

Your Shaver's Vinyl Vertical Curtain Door is a high quality, high performance flexible door system based on proven components and our many years of experience in the vinyl partition fabrication business. We are confident that it will bring you and/or your customers years of reliable and trouble-free service.

Your specific system is a vinyl motorized roll-up curtain door with face-mount bracketry. The “back-to-back” mounting dimension for your vertical extrusions will be the door opening width plus 8” (eight inches). The vertical extrusions are cut to the same height as your stated door opening, which will place the entire motorized roll, upper bracketry, and valence box above the door header. We have selected a horizontal stiffening extrusion diameter of .75”.

Unpacking and Inspection:

Please unpack your systems carefully and notify the factory immediately if there are any shortages or if any items have been damaged during transit. Your kit(s) should have all of the necessary hardware and components for a complete installation with the following exceptions (installer-provided hardware):

1. Mounting hardware for securing the custom extrusions and bracketry to the building fascia.
2. Hardware and conduit associated with the professional electrical installation of the 115VAC source power.