



SOFT-WALL & MACHINE PROTECTION SOLUTIONS

Shaver Industries - G2 Model 3600

<p>Motor:</p> <ul style="list-style-type: none"> ▪ 36" per second High Speed External Operator ▪ 110 Volt Motor ▪ 160 Cycles per hour ▪ Chain Hoist Override in Case of Power Failure ▪ Nema 1 Control Standard 	<p>Features:</p> <ul style="list-style-type: none"> ▪ Automatically re-sets after blow-out ▪ Safety photo eye ▪ Easily replaceable, exchangeable heat sealed panels available in solid vinyl, mesh, & clear PVC <ul style="list-style-type: none"> ○ 11 oz Mesh: 17 x 11 polyester scrim provides small openings difficult for insects to penetrate & provides a 65% shade factor to lower temperature and save energy. ○ 18 oz coated colored Vinyl ○ 40 Mil double polished clear PVC ▪ Resistant to all ultraviolet rays and is rot, tear and mildew resistant ▪ Meets NFPA 701 and California Fire Marshal Standards for flame retardancy ▪ Custom fiberglass pultrusions bend if loaded, won't kink or break ▪ Vinyl PVC Weather Stripping side seals & baffle ▪ Custom aluminum extrusions ▪ Upper box completely assembled at factory for easy & fast installation ▪ Valance panel made from 18 oz. coated vinyl helps keep debris out while protecting the roller tube assembly
---	--

Additional Items Offered:

Item
Additional Nema 1 – 3 Button (for external motor)
Additional Nema 4 – 3 Button
Pull Cord
RF Receiver for 3600
RF Transmitter 3-button for 1800, 2800, 3600, 5400 (requires receiver)
RF Transmitter 1-button for 1800, 2800, 3600, 5400 (requires receiver)
Motion Detector (for doors 11'7" high or taller)
Motion Detector (for doors 11'6" high or shorter) – 6'6" min
Motion Detector Remote Programmer
Additional Retro Reflective Photo Eye
Weather Cover for External Motor (Right Hand)
Weather Cover for External Motor (Left Hand)